



STAINLESS STEEL FITTINGS, VALVES AND CUSTOM FABRICATIONS

<b>AC13HP Torque Bolts to 20 FT-LB</b>							
<b>Pressure Rating (PSI)</b>							
<b>Temperature (°F)</b>	<b>Size Tube OD</b>						
	1"	1.5"	2"	2.5"	3"	4"	6"
70	1500	1500	1000	1000	1000	800	300
250	1200	1200	800	800	800	600	200

<b>AC13HH Torque Wing Nut to 25 IN-LB</b>							
<b>Pressure Rating (PSI)</b>							
<b>Temperature (°F)</b>	<b>Size Tube OD</b>						
	1"	1.5"	2"	2.5"	3"	4"	6"
70	500	500	450	400	350	300	150
250	300	300	300	200	195	150	75

<b>AY13IS Metal to Metal Contact When Tight</b>							
<b>Pressure Rating (PSI)</b>							
<b>Temperature (°F)</b>	<b>Size Tube OD</b>						
	1"	1.5"	2"	2.5"	3"	4"	6"
70	700	700	450	450	350	200	150
250	250	250	250	200	150	125	100

<b>AV13HH Torque Wing Nut to 25 IN-LB</b>							
<b>Pressure Rating (PSI)</b>							
<b>Temperature (°F)</b>	<b>Size Tube OD</b>						
	1"	1.5"	2"	2.5"	3"	4"	6"
70	500	450	400	350	250	200	125
250	250	250	200	150	125	125	60

\* Pressure ratings are based on hydrostatic tests conducted using standard-molded Buna-N material gaskets, with proper assembly of the connection points, installation of ferrules, and absence of any shock pressure.